

# 3D Printing Stuff

knowledge → vomit → wiki

- [New Printer Marlin Setup](#)

## Useful Links

- [Ellis' Printer Tuning Guide](#)
- [Voron Documentation](#)
- [gcode viewer](#)
- [Design for 3D Printing](#)

## Esteps Calib

- Load Filament (bright color recommended)
- Find out M92 E esteps with M503
- From base of extruder, mark point at 120mm/12cm
- Set local coords and extrude 100mm@1mm/s

```
M83          ; E relative mode
G1 E100 F60 ; Extrude 100mm @ 1mm/s (60mm/min)
```

- When extrusion finished, measure from base to mark.
- Calculate new esteps using previous measurement  $x$ :  $E_{\text{new}} = E_{\text{orig}} \cdot \frac{100}{120-x}$
- Set new value with M92 (ie. M92 E421).

## X/Y Offset (Marlin)

```
G28          ; home
G0 X[x offset] Y[y offset] ; move to proper bed origin
M428        ; set current pos as bed origin
M500        ; write to EEPROM
```

## Marlin UBL

Kinda nice compared to Bilinear, but its poorly explained... Firstly, manually level. Next:

```
G28          ; home
G29 P1       ; auto probe
G29 P3       ; interp. pts
G29 F10.0    ; set fade height to 10mm
```

```
G29 S0      ; save mesh in slot 0  
M500       ; save to EEPROM
```

Then for start gcode excerpt

```
G28         ; home all axes  
G29 L0     ; load mesh slot 0 (enables UBL so G29 A is redundant)  
G29 J2     ; 4-pt co-planar mesh align level
```

From:

<https://memex.kyaruc.moe/> - **kyaruc memex**

Permanent link:

<https://memex.kyaruc.moe/3dp>

Last update: **2026-06-24 Wed 03:31**

