

Artix/Arch install

First of all this is a good video guide:¹⁾ https://vid.puffyan.us/watch?v=nCc_4fSYzRA

Pre-steps

For sake of completeness:

- Grab a iso from [artixlinux.org downloads page](https://artixlinux.org/downloads)
- Flash to a usb
- Disable secure boot on the target machine (backup keys too)
- Plug in & boot (live passwd is 'artix')
- `$ su root`

Now for some hardware checks, most modern systems will be running some form of EFI for the system firmware, if the following command *fails* you **do not** have a efi system.

```
artix-live:[root]:~# ls /sys/firmware/efi/efivars/
```

However if it spits out a lotta rubbish then you **do** have an efi system.

Finally, you want to make sure you are connected to the internet, if its a wired connection, you should be good to go, but if you are on wifi, youll have to manually turn it and connect (at least in the xfce image).

Partitioning

Find your target drive with `lsblk`, generally sepaking it will *most likely* be `/dev/sda`

```
artix-live:[root]:~# lsblk
NAME MAJ:MIN RM  SIZE RO TYPE MOUNTPOINTS
loop0  7:0    0   73.2M  1 loop /run/artix/sfs/livefs
loop1  7:1    0   1.5G   1 loop /run/artix/sfs/rootfs
sda    8:0    0  931.5G  0 disk
sdb    8:16   1   29.3G  0 disk
├sdb1  8:17   1   1.6G   0 part /run/artix/bootmnt
└sdb2  8:18   1     4M   0 part
```

In the above example `/dev/sda` will be the target drive for the install.

Now most systems when partitioning will have the following set of partitions:

- `/boot` boot partition, 512MiB is the minimum size it should be, fs is FAT32 (required for efi systems)
- `/` root partition (most likely ext4)
- `[SWAP]` should be the same size as your system memory²⁾ but I usually just set it to half my

total mem size.

Now some systems *also* have 1 more more of the following partitions:

- /home to make hopping easier, all the user files are here
- /var dunno why, but probably because it has just a high a count of read/write to justify placement on another disk in certain cases

However this is my *usual* partition scheme

- / (40-80GB)
- [SWAP] ({total mem}/2)
- /home rest of disk

Now run `fdisk` on the drive to format. The following is a creation of the boot partition, but the process is the same for literally everything else.

```
artix-live:[root]:~# fdisk /dev/sda

Welcome to fdisk (util-linux 2.38.1).
Changes will remain in memory only, until you decide to write them.
Be careful before using the write command.

Device does not contain a recognized partition table.
Created a new DOS disklabel with disk identifier 0xcfc381f3.

Command (m for help): n
Partition type
   p   primary (0 primary, 0 extended, 4 free)
   e   extended (container for logical partitions)
Select (default p): p
Partition number (1-4, default 1):
First sector (2048-1953525167, default 2048):
Last sector, +/-sectors or +/-size{K,M,G,T,P} (2048-1953525167, default
1953525167): +512M

Created a new partition 1 of type 'Linux' and of size 512 MiB.
```

tips:

- p to list partitions
- q to quit **without** writing changes
- w to quit **and write changes**

When you finish, double check the scheme, then write changes. The below is the scheme for a efi system.

```
Command (m for help): p
Disk /dev/sda: 931.51 GiB, 1000204886016 bytes, 1953525168 sectors
Disk model: Samsung SSD 870
Units: sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
```

```
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disklabel type: dos
Disk identifier: 0xcfc381f3
```

Device	Boot	Start	End	Sectors	Size	Id	Type
/dev/sda1		2048	1050623	1048576	512M	83	Linux
/dev/sda2		1050624	126879743	125829120	60G	83	Linux
/dev/sda3		126879744	1953525167	1826645424	871G	83	Linux

Filesystems

With the above scheme, you can make the following filesystems on the partitions:

```
# if your system is efi, you *will* need a boot partition
# it is also *required* that it is a FAT32 filesystem
mkfs.fat -F32 /dev/sda1

# the rest of the disks get a normal filesystem like ext4
mkfs.ext4 /dev/sda2
mkfs.ext4 /dev/sda3
```

Mounting & OS Bootstrap

Next we need to mount the filesystems so that we can install the os

```
# first the root partition
mount /dev/sda2 /mnt

# then make the mountpoints for the other 2 fs
mkdir -p /mnt/{boot,home}
mount /dev/sda1 /mnt/boot
mount /dev/sda3 /mnt/home
```

Now time for the install part, you will run `basestrap` with the path to the root and a list of packages along with `base`, `base-devel`, and `linux`. The following other packages I recommend installing:

- `linux-firmware`: all of your hardware blobs so that your system can run
- `runit`: the only good init system³⁾
- `elogind-runit`: `elogind` for above `init`
- `vim`: good editor
- `git`: source control for installing aur pkgs
- `librewolf`: webbrowser

```
basestrap /mnt base base-devel linux linux-firmware runit elogind-runit
```

Finally, before we `chroot`, we need to generate our `fstab` for boot filesystems.

```
fstabgen -U /mnt >> /mnt/etc/fstab
```

Artix Chroot

Now that we have a system, lets chroot in:

```
artix-chroot /mnt
```

Pacman mirrors setup

Edit the mirrorlist for pacman to get slight faster speeds:

```
vim /etc/pacman.d/mirrorlist
```

Locale Setup

Depends on where you live, but you need to link the timezone info. For example

```
ln -sf /usr/share/zoneinfo/America/New_York /etc/localtime
```

Now set the system clock to hardware

```
hwclock --systohc
```

Now finally setup the locale, first edit and find your locale (the us for example is en_US) uncomment **both** UTF-8 & ISO-8859-1 variants. Then run locale-gen.

```
vim /etc/locale.gen  
locale-gen
```

Now edit /etc/locale.conf (this should be a new file. For example from locale.gen

```
echo "LANG=en_US.UTF-8" > /etc/locale.conf
```

Networking

First install some networking packages

```
pacman -S networkmanager networkmanager-runit
```

Then enable it for boot, runit of course:

```
ln -s /etc/runit/sv/NetworkManager/ /etc/runit/runsvdir/current
```

Now edit your machines hostname:

```
vim /etc/hostname
```

Finally the hosts file.

```
vim /etc/hosts
```

People put a variation of things here, but the following are **highly recommended**⁴⁾

```
127.0.0.1    localhost
::1         localhost
```

I also like to put the following line in as well (not \$hostname this should be the hostname in /etc/hostname)

```
127.0.0.1    ${hostname}.local $hostname
```

Bootloader

Now, its finally time to make our machine bootable, we need to install our bootloader grub. os-prober is required if you want to dual-boot and efibootmgr is required if you are installing an efi system.

```
pacman -S grub os-prober efibootmgr
```

Now we install grub and generate the grub config

```
grub-install --target=x86_64-efi --efi-directory=/boot --bootloader-id=GRUB
grub-mkconfig -o /boot/grub/grub.cfg
```

Finally, set the root password:

```
passwd
```

1)

The arch manual sucks really bad

2)

Some people recommend double, but I've never seen that in the wild

3)

You can also install whatever you want for an init

4)

Required imo

From:

<https://memex.kyaruc.moe/> - **kyaruc memex**

Permanent link:

https://memex.kyaruc.moe/guide:artix_arch_install?rev=1683926358

Last update: **2023-05-12 Fri 21:19**

